



VIBFAST PIGMENTS PVT. LTD.

C-1, 91/6, Phase 1, G.I.D.C., B/h. Bank of India, Vatva, Ahmedabad-382 445, INDIA

Phone : 0091-79-32920774, 0091-79-64501424 Fax : 0091-79-25893014

Website : www.vibgyorchemtex.com E-Mail : amit@vibfast.com

TECHNICAL DATA SHEET

PRODUCT C.I. NAME.	:	PIGMENT RED 122
C.I. NO.	:	73915
CUST.TARRIF NO.	:	3204 17 39
APPLICATION	:	NC LACQUER, PRINTING INK, PAINTS, PLASTICS, RUBBER, TEXTILE

PHYSICAL PROPERTIES

Density (g/cm ³)	:	1.0
Moisture Contents	:	< 1%
Salt Content	:	< 1%
Oil Absorption	:	67
Sieve Residue (300 Mesh)	:	0.5%
pH Of Aqueous Extract	:	7
Heat Stability (°C/5min)	:	270
Bulk Volume (ml/100g)	:	3
Grit Content	:	Less than 500 ppm
Heavy Metal, & PCB Content	:	Complying to EN 71-3 and AP (89) of European regulation.
Powder Appearance	:	Dry Bluish Red Powder
Hazardous ingredients	:	Nil
Toxicological properties	:	Non toxic
Shelf Life	:	5 Years

FASTNESS PROPERTIES (1-5) Scale ; 1 Poor - 5 Excellent

Water	:	5
Xylene	:	5
Ethanol	:	4-5
White spirits	:	5
Methyl Ethyl Ketone	:	4-5
Butyl Acetate	:	4-5
Butyl Glycol	:	4-5
Butanol	:	4-5
Acid	:	5
Alkali	:	5

LIGHT FASTNESS (1-8 Scale ; 1 Very Low - 8 Outstanding)

Full Shade	:	8
Tint Shade	:	8